Post Graduate Institute of Veterinary Education and Research (PGIVER) F.6. () IPBIIVER I Punch 12025/3045 Date: 01-02-2025

CORRIGENDUM - 01

(Open Bid -04 for Aluminum Partitioning & Fabrication work with material and Labour at PGIVER PREMISES 2024-25)

With reference to various representations received in the Pre-Bid Meeting held on 01-02-2025, and subsequent inputs from users, the following modification/amendments in the Tender Document are being incorporated and considered.

Amendments in Technical Specifications:

S.No.	Name of Item	Amended Specifications	Quantity
1.	Aluminum Partitioning of Lab Spaces (Pathology Department)	 Partition Sections" made of Powder-coated (cream/off-white) Aluminum RECTANGULAR PIPES (Pipe/ section size Minimum 1.5 inch x 2.5 inch dimension by sections of good quality having atleast 2.8 - 3.2 kg per 16 ft section length; Single Glaze & Double Glaze as required) (Aluminum section quality of Omalco or equivalent make) Plain Glass (approx. 4.5 to 5 mm thick) (Saint Gobain, Modi,or equivalent); Rubber Bidding to be used of good quality like TVS Grade or equivalent) Particle Board (minimum 11-12 mm thick) to be used in lower panel only upto 3-4 feet from ground. Inclusive of All Hardwares & accessories (including rubber packing, snap beading, PVC/ neoprene felt, etc. angles, clamps, hinges, door handles, door stoppers, ceiling supports, rawl plugs, screws or with fixing clips, or with expansion hold fasteners, silicon sealants, wherever required) Inclusive of Designing, Fitting, Finishing, Cleaning and Labour and any other charges Approx area of 1500 sq. ft Board 5' DOORS: Total- 07 Door (six single doors of 3' x 6.5'feet and; one door of double palla 2.5' x 6.5'feet and 2.5' x 6.5'feet) Doors to be made of Al section of approx 3.25 x 1.75 inch dimension by sections of good quality having atleast 4.8 ± 0.3 kg per 16 ft section length. NO BASE MOTORS Required, but Door Closures needed. All door section to be made "with MS Rod" support on Top and Bottom 	Approx 1500 sq ft of partitioning
2.	Aluminium Partitioning in Hostels	 Approx area of 960 sq. ft. (Approx 180 Sq ft at the entrance and 780 Sq ft in the Mess) for aluminium partitioning including gates. Partition Sections" made of Powder-coated (cream/off-white) Aluminum RECTANGULAR PIPES (Pipe/ section size Minimum 1.5 inch x 2.5 inch dimension by sections of good quality having atleast 2.8 - 3.2 kg per 16 ft section length; Single Glaze & Double Glaze as required) (Aluminum section quality of Omalco or equivalent make) Plain Glass (approx. 4.5 to 5 mm thick) (Saint Gobain, Modi,or 	Approx 1000 sq ft of partitioning

Page 1 of 3

		equivalent); Rubber Bidding to be used of good quality like TVS	
AL S	a59hatotoset	Crada ar equivalent)	
	as contra and	4. Particle Board (minimum 11-12 mm thick) to be used in lower	
		panel only upto 3-4 feet from ground. 5. Inclusive of All Hardwares & accessories (including rubber	
		packing, snap beading, PVC/ neoprene felt, etc. angles, clamps,	
		hinges, door handles, door stoppers, ceiling supports, rawl plugs,	
		screws or with fixing clips, or with expansion hold fasteners,	
		-iliaan sealants wherever required)	
		6. Inclusive of Designing, Fitting, Finishing, Cleaning and	
		Labour and any other charges.	
		DOORS:	
		Total 03 Door (single doors of 3' x 6.5'feet)	ea.
		Dears to be made of Al section of approx 3.25 x 1.75 men	and I
		timengion by sections of good quality having atleast 4.0 ± 0.5	
		kg per 16 ft section length. NO BASE MOTORS Required,	
		but Door Closures needed.	
		All door section to be made " with MS Rod" support on Top	
	A 1 1000	and Rottom	
		Approx area of 820 sq. ft. for aluminum partitioning including	
		gates. Partition Sections" made of Powder-coated (cream/off-white).	
		A Lucioum DECTANGIII AR PIPES (Pipe/ section size Minimum)	
		15 inch v 25 inch dimension by sections of good quality having	
		1 20 22 kg ner 16 ft section length; Single Glaze &	
		Double Glaze as required) (Aluminum section quality of Omalco	
		wivelent make)	
		Plain Class (approx 45 to 5 mm thick) (Saint Gobain, Woul, or	
		equivalent); Rubber Bidding to be used of good quality like TVS	
		Crade or equivalent)	
	Aluminium	Particle Board (minimum 11-12 mm thick) to be used in lower	Approx
	THE RESERVE THE PARTY OF THE PA	panel only upto 3-4 feet from ground.	0.50 0 0
2	Partitioning of	Inclusive of All Hardwares & accessories (including rubber packing, snap beading, PVC/ neoprene felt, etc. angles, clamps,	850 sq ft of
3.	AH- Extension	packing, snap beading, FVC/ heopitche lett, etch day, hinges, door handles, door stoppers, ceiling supports, rawl plugs,	partitioning
	Department	screws or with fixing clips, or with expansion hold fasteners,	
		ailian caplants wherever required)	
		Inclusive of Designing, Fitting, Finishing, Cleaning and Labour	
	Decision September	and any other charges.	
		DOODS.	
	100 TELL 25	• Total- 04 Door (Two single doors of 3' x 6.5'feet; and Two door	
	Q to E 3 textiliz	Camble nelle 25' v 6 5' teet and 2.3 x 0.3 lett	
		All Jan gootion to be made " with MS Kod Support on Top and	
		Bottom Doors to be made of Al section of approx 3.25 x 1.75 inch dimension by sections of good quality having atleast 4.8 ±	
	SE SENSE	o.3 kg per 16 ft section length. NO BASE MOTORS Required,	
		but Door Closures needed.	
	3,0000 500 5	Aluminium partition work (110 square feet)	
		(10-11 cm ft)	
	Aluminium	Powder-coated (creamon-winte)	1500
	Partitioning of	Aliminum PECTANGIII AR PIPES (Pipe/ section size Williamin	12039 100
4.	Microbiology	1 5 inch v 2 5 inch dimension by sections of good quality having	partitioning
1.	Department	2 2 kg per 16 ff section length; Single Glaze &	
	Department	Double Glaze as required) (Aluminum section quality of Omalco	
		or equivalent make) Plain Glass (approx. 4.5 to 5 mm thick) (Saint Gobain, Modi,or	
		Pag	10 2 of 3
		Desaired	M
		m to the	
		(1765ar	
		0/	

equivalent); Rubber Bidding to be used of good quality like TVS Grade or equivalent) Particle Board (minimum 11-12 mm thick) to be used in lower

panel only upto 3-4 feet from ground.

Inclusive of All Hardwares & accessories (including rubber packing, snap beading, PVC/ neoprene felt, etc. angles, clamps, hinges, door handles, door stoppers, ceiling supports, rawl plugs, screws or with fixing clips, or with expansion hold fasteners, silicon sealants, wherever required)

Inclusive of Designing, Fitting, Finishing, Cleaning and Labour and any other charges.

DOORS:

- Total- 01 Door (single doors of 3' x 6.5'feet)
- Doors to be made of Al section of approx 3.25 x 1.75 inch dimension by sections of good quality having at least 4.8 ± 0.3 kg per 16 ft section length. NO BASE MOTORS Required, but Door Closures needed.
- All door section to be made "with MS Rod" support on Top and Bottom

Total Area of Aluminum partition work (1+2+3+4)

Approx 3500 sq ft

The above modified technical specifications will be considered for Open Bid-04 and final evaluation.

(Chauthma)

Member

Sr. A.O. (Retd.)

In-charge Store.

Member

Member

(Dr. Anurag Pandey)

Convener

I/c. Purchase